

epic safes - Nova range

Epic NOVA Safe
Suggested cash rating
£4,500

Body

Inner and outer body are constructed from 2.2mm high grade steel welded together to form one solid unit. The cavity between the inner and outer lining which is 50mm is filled with a solid fire and theft resistant monolith. Safes fire resistant to 30 minutes

Door

An 82mm total thickness constructed with 10mm steel plate.

Boltwork

Base fixing as standard. Front moving bolts and rear dog bolts are made from 30mm solid steel that lock securely into the inner lining.
 2 front moving bolts
 N1412, N1616, N1812
 3 front moving & 3 fixed rear dog bolts N2316, N2916
 4 front moving & 4 fixed rear dog bolts on model NN3520

Locking

The door is locked using a high quality lock with an additional anti-explosive (AED) device which is permanently in place ready to activate should an attack occur.

Contact Us

Tel. 01952 684855
sales@epicsafes.co.uk

Take a look at the complete range of Epic Safes at

www.epicsafes.co.uk



Epic Safes & Security UK Ltd
 Unit D6
 Court 2000 Industrial Estate
 Bridgnorth Road
 Madeley Telford
 England TF7 4JB



epic safes - handmade in telford

The Epic Safe range is made from high grade steel and manufactured under the quality control procedures of ISO 9001 - 2000

Ref	External			Internal			KG
	H	W	D	H	W	D	
N1412	455	400	355	355	300	260	120
N1416	506	505	556	406	406	406	190
N1812	555	400	400	455	300	260	140
N2316	680	500	520	580	400	380	225
N2916	830	500	520	730	400	380	260
N3520	990	600	620	890	500	480	320
R5020	1350	600	620	1250	500	480	525

allow an extra 65mm depth for the safe handle

Your Local Dealer