

epic safes - Stanmore range

Epic STANMORE Safe
Suggested cash rating
£3,000

Body

Inner and outer body are constructed from 2.2mm BS grade steel welded together to form one solid unit. The cavity between the inner and outer lining which is 50mm is filled with a solid fire and theft resisting monolith. Fire resistant to 30 minutes. Base fixings as standard.

Door

Constructed using 8mm solid steel plate with an overall thickness of 78mm.

Boltwork

Front moving and fixed dog bolts are made from 30mm solid steel that lock securely into the lining.
 2 front moving & 2 fixed on:
 S1412, S1616, S1812
 3 front moving & 3 fixed on:
 S2316, S2916.

Locking

The door is locked using a high quality lock with an additional anti-explosive device (AED) which is permanently in place ready to activate should an attack occur.

Contact Us

T. 01952 684855
sales@epicsafes.co.uk

Take a look at the complete range of Epic Safes at

www.epicsafes.co.uk



Epic Safes & Security UK Ltd
 Unit D6
 Court 2000 Industrial Estate
 Bridgnorth Road
 Madeley Telford
 England TF7 4JB



epic safes - handmade in telford

The Epic Safe range is made from high grade steel and manufactured under the quality control procedures of ISO 9001 - 2000

Ref	External			Internal			KG
	H	W	D	H	W	D	
S1412	455	400	400	355	300	260	115
S1616	506	505	556	406	406	406	185
S1812	555	400	400	455	300	260	135
S2316	680	500	520	580	400	380	220
S2916	830	500	520	730	400	380	255
S3520	990	600	620	890	500	480	315
S5020	1350	600	620	1250	500	480	515

allow an extra 65mm depth for the safe handle

Your Local Dealer

To enable continued product development we reserve the right to alter the specification without notice. All measurements must be considered as approximate.